

# ACTUATION LIMIT SWITCH BOXES



## Specification

- 1 Model KLS-820M.
- 2 Enclosure: weatherproof IP67.
- 3 Solid and compact design.
- 4 Bolts on visual position indicator (re-adjustment available upon required direction).
- 5 Dual cable entries: 2 x 1/2" NPT (Standard) M20, PG13.5, PF1/2", PF1/2" (option).
- 6 Terminal strips: 8 points (0.08 – 2.5mm<sup>2</sup>).
- 7 Captive cover Bolts.
- 8 Easy mounting.
- 9 NAMUR standard stainless steel shaft and bracket.



## Material

Housing Cover & Body	Aluminium Die Cast
Shaft	Stainless Steel
Indicator Cover	Polycarbonate
Cam	Polycarbonate
Spring	Stainless Steel
Housing Cover Bolt	Stainless Steel
O-ring	NBR
Bushing	Bronze
E-ring(shaft)	Stainless Steel
Earth Lug	Stainless Steel
Indicator	ABS/Polycarbonate
Bracket	Stainless Steel

## Position Monitor

- 1 Continuous visual position indicator.
- 2 Made of high impact, heat, chemical resistance and transparent carbonate.
- 3 Excellent corrosion protection, high visibility and reliability

## Dimensions

